



# 834 EPB



4  
3  
8

## **Automatic straight slicing machine**

- From wafer-thin slices to 5 mm slices
- Fully automatic slicing, stacking and arranging as tiles
- Integrated sharpening unit; fast and easy sharpening of the blade
- Options: available with a Teflon layer
- Available with a conveyor and/or mobile table

# Deko 834 EPB

## Use of material

s/s 303/304 for all parts that come into contact with food  
Anodised aluminium

## Dimensions

**Foot print:** (L x W) 500 x 400 mm

**External dimensions:** (L x W x H) 740 x 900 x 590mm

**Dimensions of meat table:** (L x W) 460 x 240mm, standard version  
Can be tilted, protected



**Sharpening unit:** Removable and integrated into the slicing machine  
Fast and easy sharpening of the blade

**Slicing capacity:** 190mm for round products  
190 x 190mm for square products  
195 x 190mm for rectangular products  
Maximum length: 460mm

**Blade:** Ø 296mm  
Blade speed: 280 RPM  
Special hard, chromium-plated circular blade  
Also available in s/s, Teflon version and as a serrated model

**Thickness adjustment:** 0 – 5mm, infinitely adjustable

**Speeds:** Adjustable: 25 - 45 or 55 movements per minute

**To be adjusted to:** Stacking - max. stacking height 70mm  
Arranging as tiles  
Distance between slices is adjustable  
Maximum length of arranging as tiles 280mm  
Ongoing adjustment

**Product carriage:** Keeps the product in its place  
Result: minimal loss due to cutting

**Cleaning:** The transporter, stacker arm, rest slicer, pin plate, blade plate and collection table are removable

**Motor:** 0.180kW - 1 speed - belt drive  
1,400 RPM  
IP 23  
Emergency stop switch included



## Models and options

**834 EPB Conveyor:** This model is supplied with a:  
• Small conveyor belt with a length of 750mm or a  
• Large conveyor belt with a length of 1,400mm.

**834 EPB Teflon:** This model features a high-quality Teflon layer for parts that come into contact with food  
Especially suitable for slicing cheese.

**834 EPB Teflon Conveyor:** Specs similar to 834 EPB Teflon, including a small or large conveyor belt

**Mobile table:** All slicer models can be supplied with a

**Voltage:** 230V – 50Hz 1 Phase 6 Ampere  
400V – 50Hz 3 Phase 0.6 Ampere  
115V – 60Hz 1 Phase 4.5 Ampere

**Noise level:** < 60 dB (A)

**Weight:** 93kg

**Meets:** CE Directive 98/37/EEC  
• European standard: EN 60204-1:1992  
EMCL 89/336/EC  
• EN 50081-1:1992  
• EN 50082-1:1192 Safety and hygiene requirements EN 1974 / 1998

**Warranty:** 12 months as from delivery  
Does not apply to parts that are subject to wear

